

(19) World Intellectual Property
Organization
International Bureau



13 DEC 2004



(43) International Publication Date
8 January 2004 (08.01.2004)

PCT

(10) International Publication Number
WO 2004/002672 A1

(51) International Patent Classification⁷: **B23K 26/38**

(21) International Application Number:
PCT/US2003/014468

(22) International Filing Date: 6 May 2003 (06.05.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0214990.4 28 June 2002 (28.06.2002) GB

(71) Applicant (for all designated States except US): **3M INNOVATIVE PROPERTIES COMPANY** [US/US]; 3M Center, P.O. Box 33427, Saint Paul, MN 55133-3427 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **LOW, David, K., Y.** [SG/SG]; Block 277, Bangkit Road, #08-114, 670277 Singapore (SG).


(74) Agents: **RINGSRED, Ted, K.** et al.; Office of Intellectual Property Counsel, P.O. Box 33427, Saint Paul, MN 55133-3427 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,

[Continued on next page]

(54) Title: MANUFACTURE OF VALVE STEMS



(57) Abstract: A method for providing a hole into a valve component having an internal cavity (55), said method comprising the steps of filling and sealing a fluid (59) within said cavity; and laser drilling the hole through the component into the internal cavity. Said method is particularly advantageous for providing a side port into a valve stem (54). The present invention also relates to a method of manufacturing a valve stem, said method comprising the steps of: a) providing a valve stem work-piece having a passageway with an outlet (57); b) filling the passageway with a fluid; c) sealing the outlet; d) laser drilling a side port through the work-piece into the passageway; and e) unsealing the outlet.

WO 2004/002672 A1



SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*